

Diesel Forklift 4-5 Ton

Model	Unit	FD40T	FD45T	FD50ST
Power Type	-	Diesel		
Load Capacity	kg/lb.	4000/8800	4500/9900	5000/11000
Load Center	mm/in.	500/19.7	500/19.7	500/19.7
Max.Lift Height	mm/in.	3000/118.2	3000/118.2	3000/118.2
Free Lift Height	mm/in.	150/5.91	150/5.91	150/5.91
Fork Size(L*W*T)	mm/in.	1070x150x55/41.73x5.91x2.17		
Tilt Angle(Fwd/Bwd)	deg	6/12	6/12	6/12
Length to Fork Face	mm/in.	3091/121.79	3091/121.79	3125/123.13
Overall Width	mm/in.	1485/58.51	1485/58.51	1485/58.51
Overall Height Fork Raised	mm/in.	4250/167.45	4250/167.45	4250/167.45
Overhead Guard Height	mm/in.	2290/90.23	2290/90.23	2290/90.23
Min.Right Angle Aisle Width	mm/in.	3415/134.55	3415/134.55	3460/136.32
Turning Radius (outside)	mm/in.	2790/109.93	2790/109.93	2830/111.50
Travel Speed(with/without)	km/h	22/20	22/20	22/20
Lifting Speed(with/without)	mm/h	480/450	480/450	480/450
Max.Grade Ability	%	20	18/	17
Ground Clearance:Mast	mm/in.	145/5.71		
Ground Clearance:Frame	mm/in.	180/7.09		
Wheelbase	mm/in.	2000/78.8		
Tread (Front/Rear)	mm/in.	1180(46.49)/1190(46.89)		
Self Weight	kg/lb.	6450/14190	6770/14894	7050/15510
Engine Model	-	MITSUBISHI S6S		
Rated Output	kw/r.p.m	55.3/2450		
Rated Torque	NM/r.p.m	240/1600		
Displacement	cc	4996		

FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address:

